

REMARKS


Original claims 1-3 have been amended in this application to clarify the subject matter of the invention as compared to the original, canceled claims.

The abstract has been amended to correct various typographical, grammatical and idiomatic informalities, and to place the application into proper conformance with U.S. patent practice.


In light of the foregoing, it is respectfully submitted that the application is in proper form for allowance of all claims and notice to that effect is earnestly solicited.

Respectfully submitted,

Jordan and Hamburg LLP

By 
C. Bruce Hamburg
Reg. No. 22,389
Attorney for Applicants

and,

By 
T. David Bomzer
Reg. No. 48,770
Attorney for Applicants

122 East 42nd Street
New York, New York 10168
(212) 986-2340

DESCRIPTION**~~TITLE OF THE INVENTION~~****RAIL FIXING PART STRUCTURE****~~TECHNICAL FIELD~~ BACKGROUND OF THE INVENTION**

5 The present invention relates to a rail fixing part structure of a drawer that houses clothing and the like.

~~BACKGROUND ART~~

 Conventionally, chests are used on an occasion of housing clothing and the like.

10 The chest is constructed by a chest body made of a synthetic resin and a drawer made of a synthetic resin which is housed in the chest body to be able to be drawn.

 When the chest body is changed to a wooden one in such a chest, the drawer made of a synthetic resin slides in contact with the wooden chest body.

15 This brings about the problem of worsening slide of the drawer and reducing the operability.

 In order to solve the problem, it is conceivable that a drawer part supported by the chest body is constructed by a metal rail.

 However, in such a drawer, the metal rail has to be mounted to the
20 drawer made of the synthetic resin, thus requiring labor and efforts.

The present invention is made in view of the above conventional problems, and an object of the present invention is to provide a rail fixing part structure easy in mounting operation.

DISCLOSURE BRIEF SUMMARY OF THE INVENTION

5 In order to solve the above described problems, in a rail fixing part structure of claim 1 of the present invention, in a rail fixing part structure in which a metal rail that slidably supports a drawer at a body is fixed to the drawer of a synthetic resin that is housed in the body to be able to be drawn, a flange, which extends toward the aforesaid drawer, is provided at the aforesaid
10 rail, while ribs which vertically sandwich the aforesaid flange are provided at a side surface of the aforesaid drawer.

Namely, on the occasion of fixing the metal rail to the drawer of the synthetic resin, the flange provided at the rail is inserted between the ribs which are provided at the flange, and the above described flange is vertically
15 sandwiched with the ribs. Thereby, the above described rail is locked at the drawer.

Besides, in the rail fixing part structure of claim 2, a support surface which extends along the aforesaid flange is provided at an upper end portion of the rib which supports a lower surface of the aforesaid flange.

MARKED SPECIFICATION

F-8789

Ser. No.

Namely, in the ribs which vertically sandwich the flange provided at the rail, the support surface which extends along the above described flange is provided at the upper end portion of the rib which supports the lower surface of the above described flange. Thereby, the fixed state of the flange is stabilized.

5 Further, in the rail fixing part structure of claim 3, a screw-in part in which a screw that is inserted through the aforesaid flange is screwed in the state in which the aforesaid flange of the aforesaid rail is sandwiched between the aforesaid ribs is provided at the aforesaid drawer.

10 Namely, the drawer is provided with the screw-in part in which the screw inserted through the above described flange is screwed is provided, and by screwing the above described screw into the above described screw-in part, the flange of the above described rail is fixed in the state in which the flange is sandwiched with the ribs of the drawer.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Accompanying the specification are figures which assist in illustrating the embodiments of the invention, in which:

FIG. 1 is a front view showing one embodiment of the present invention. FIG. 2A is a plane view of the same embodiment—;

FIG. 2B is a side view—;

20 FIG. 3 is a perspective view showing a rail in the same embodiment—;

____ FIG. 4 is a side view showing a drawer body in the same embodiment;
; and

____ FIG. 5 is a side view showing a section of a folded part of the drawer body in the same embodiment.

5 **~~BEST MODE FOR CARRYING OUT~~ DETAILED DESCRIPTION OF**
THE INVENTION

In order to explain the present invention in more detail, the present invention will be explained hereinafter with reference to the attached drawings.

10 Fig. 1 is a view showing a chest 1 including a rail fixing part structure according to an embodiment, and the chest 1 houses clothing and the like.

15 The chest 1 is constructed by a wooden chest body 11 and drawers 12 made of a synthetic resin. The above described chest body 11 is formed into a rectangular shape by a bottom plate 14 provided with leg parts 13, side plates 15 and 15 vertically provided at both side portions of the bottom plate 14, a back plate 16 vertically provided at a back side of the above described bottom plate 14, a top plate 17 provided at an upper end of the above described side plates 15 and 15, and the above described back plate 16, as shown in Fig. 1 and Fig. 2. Three of the above described drawers 12 are housed in a front opening of the chest body 11 to be able to be drawn, and are constructed to be able to
20 house and store material goods in the drawers 12.

MARKED SPECIFICATION

F-8789

Ser. No.

The above described drawer 12 is constructed by a drawer body 21 in a rectangular container shape, and a front plate 22 mounted in the state in which it is locked at claw parts 21a and 21a (see Fig. 4) of the drawer body 21, and the above described drawer body 21 and the above described front plate 22 are
5 formed to be semitransparent and constructed to be able to confirm an inside.

The front plate 22 is formed to be light blue and transparent, and the above described drawer body 21 is formed to be white and transparent. Note that the above described front plate 22 and the drawer body 21 may be formed to be not only semitransparent but also formed to be transparent, or opaque, and
10 in the case of opaque, they can be also colored. At this time, the above described front plate 22 and the above described drawer body 21 are constructed by separate pieces, and therefore, the above described front plate 22 and the above described drawer body 21 can be set to be the same color, or can be set to be different colors. As a result, the appearance quality can be
15 enhanced and variation can be increased.

A recessed part 23 is provided at a lower portion of the above described front plate 22, and a step part 24 on which a hand can be laid at the time of drawing is formed between the recessed part 23 and the ordinary part. The step part 24 is formed into a bow shape with a central portion projecting upward,

MARKED SPECIFICATION

F-8789

Ser. No.

and the operating force applied to the step part 24 is applied to a later-described rail 25 which supports the drawer 12 at the chest body 11.

5 Metal rails 25, which are supported at a rail not shown provided at an inner surface of each of the side plates 15 and 15 of the above described chest body 11 and slidably support the drawer 12 at the above described chest body 11, are fixed to both side portions of the above described drawer body 21, and the drawer body 21 opened upward has its upper end portion reinforced by the rails 25.

10 The rail 25 is formed by folding a long metal plate, and a flange 31 extending toward the above described drawer 12 is provided at the lower edge portion, as shown in Fig. 3. Screw insertion holes 32 and 32 are provided at both end portions of the flange 31 and a raised wall 33 rises from the side edge of the flange 31. A guide surface 34 extending in the direction to separate from the above described drawer 12 is provided at an upper edge of the raised wall 15 33, and a bent part 35 which is bent downward is formed at a side edge of the guide surface 34. The above described guide surface 34 is notched at one end portion of the rail 25, and a roller 37 a part of which projects from the above described guide surface 34 is rotatably supported at a region of the above described raised wall 33 in a notched part 36.

MARKED SPECIFICATION

F-8789

Ser. No.

Meanwhile, as shown in Fig. 4, the above described drawer body 21 is formed to be opened upward by a rectangular bottom surface 41, a front surface 42 raised from a front edge of the bottom surface 41, side surfaces 43 raised from both side edges of the above described bottom surface 41, and a back surface 44 raised from a rear edge of the above described bottom surface 41.

As shown in Fig. 5, an outward extending surface 45 which extends to an outside is formed at upper edges of the above described side surface 43 and the above described back surface 44, and a downward extending surface 46 which extends downward is formed at the extending surface 45. The downward extending surface 46 is constructed to be in surface contact with the raised wall 33 of the mounted rail 25 to prevent tilt of the rail 25 and form a folded portion at the upper edge portions of the above described side surfaces 43 and the above described back surface 44 to be able to reinforce them.

The folded portion is constituted of side folded portions 51 formed at the above described both side surfaces 43, and a rear folded part 52 formed over the back surface 44 from the rear portions of both the side surfaces 43, and gaps 53 are formed between the above described both side folded portions 51 and the above described rear folded part 52. As shown in Fig. 5, upper ribs 54 and 54 extending downward from the above described outward extending surfaces 45 and 45 are formed at both ends of the above described side folded parts 51 and

MARKED SPECIFICATION

F-8789

Ser. No.

both ends of the above described rear folded part 52, and the upper ribs 54 and 54 are also provided to connect to the above described side surfaces 43.

Besides, on the side surface 43, a lower rib 55 extending in the vertical direction is formed at a lower portion of the above described gap 53 between the above described side folded part 51 and the above described rear folded part 52, and on the front surface 42 side from the above described side folded part 51, the lower rib 55 extending in the vertical direction is formed. Upper ends of both the lower ribs 55 and 55 are provided at a lower position from the position of the height of the lower end of the above described upper rib 54, so that the flange 31 of the above described rail 25 can be vertically sandwiched with the above described upper ribs 54 and the lower ribs 55.

Support surfaces 61 which extend along the above described flange 31 are integrally formed at upper end portions of the above described lower ribs 55 which support the above described flange 31 from the lower surface side, and the support surface 61 is constructed to be in surface contact with the lower surface of the above described flange 31.

Besides, cylindrical screw-in parts 71 which extend downward are integrally formed at both end portions at the above described outward extending surfaces 45 of the above described both side folded parts 51 and 51. The screw-in parts 71 are provided at positions corresponding to screw insertion

holes 32 and 32 formed at the above described flange 31 in the state in which the above described rail 25 is mounted, and the lower end of the screw-in part 71 is set to have a length dimension that reaches the top surface of the above described flange 31. Thereby, tapping screws which are inserted through the
5 above described screw insertion holes 32 and 32 of the above described flange 31 can be screwed into the above described screw-in parts 71 and 71 in the state in which the above described flange 31 of the above described rail 25 is sandwiched between the above described respective ribs 54 and 55.

10 In the above described embodiment with the above construction, on the occasion of fixing the metal rail 25 to the drawer 12 of the synthetic resin, the flange 31 provided at the rail 25 is inserted between the upper ribs 54 and the lower ribs 55 provided at the drawer 12, and the above described flange 31 is vertically sandwiched with both the ribs 54 and 55. Thereby, the above described rail 25 is locked at the drawer 12.

15 By only inserting the flange 31 provided at the above described rail 25 between the respective ribs 54 and 55 provided at the drawer 12 as described above, the above described rail 25 can be locked at the drawer 12 in the state in which the above described flange 31 is vertically sandwiched between both the ribs 54 and 55. Thereby, the metal rail 25 can be easily mounted to the drawer
20 12 of the synthetic resin, and the mounting operation can be easily performed.

Besides, in the respective ribs 54 and 55 which vertically sandwich the flange 31 provided at the above described rail 25, the support surfaces 61 which extend along the above described flange 31 is provided at the upper end portions of the lower ribs 55 which support the lower surface of the above described flange 31.

Thereby, the fixed state of the above described flange 31 can be stabilized.

The screw-in parts 71 which extend downward are integrally formed at both end portions at the outward extending surfaces 45 of the both side folded parts 51 and 51 of the above described drawer 12, and the screw-in parts 71 and 71 are provided at the positions corresponding to the screw insertion holes 32 and 32 of the above described rail 25.

Therefore, the tapping screws are inserted through the screw insertion holes 32 and 32 of the above described flange 31 in the state in which the flange 31 of the above described rail 25 is sandwiched between the respective ribs 54 and 55, and the tapping screws are screwed into the above described screw-in parts 71 and 71, whereby the flange 31 of the above described rail 25 can be screwed in the state in which the flange 31 is sandwiched between the respective ribs 54 and 55 of the above described drawer 12. Thereby, fixation can be further enhanced.

~~INDUSTRIAL APPLICABILITY~~

As explained thus far, in the rail fixing part structure of claim 1 of the present invention, on the occasion of fixing the metal rail to the drawer of the synthetic resin, the flange provided at the rail is inserted into the ribs provided
5 at the drawer, whereby the rail can be locked at the drawer in the state in which the above described flange is vertically sandwiched with the ribs.

Thereby, the metal rail can be easily mounted to the drawer of the synthetic resin, and the mounting operation can be easily performed.

Besides, in the rail fixing part structure of claim 2, in the ribs which
10 vertically sandwich the flange provided at the rail, the support surfaces which extend along the above described flange are provided at the upper end portions of the ribs which support the lower surface of the above described flange, and therefore, the fixed state of the flange can be further stabilized.

Further, in the rail fixing part structure of claim 3, the screw-in parts in
15 which the screws inserted through the flange are screwed are provided at the drawer, and the flange of the above described rail can be fixed in the state in which the flange is sandwiched between the ribs of the drawer by screwing the above described screws into the above described screw-in parts. Thereby, fixation can be enhanced.

MARKED SPECIFICATION

F-8789

Ser. No.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not as restrictive. The scope of the invention is, therefore, indicated by the appended claims and
5 their combination in whole or in part rather than by the foregoing description. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

ABSTRACT OF THE DISCLOSURE

A rail fixing structure of a drawer which houses clothing and the like.

The present invention provides a rail fixing part structure easy in a mounting operation. A chest is constructed by a wooden chest body and a drawer of a synthetic resin, and a drawer body ~~21~~ is formed into a rectangular container shape. Metal rails that slidably support the drawer at the chest body are fixed to both side portions of the body ~~21~~, and flanges which extend toward the drawer are provided at rail lower edge portions. A side folded part ~~51~~ and a rear folded part ~~52~~ which are each constituted of an outward extending surface ~~45~~ extending toward an outside and a downward extending surface ~~46~~ extending downward are provided at an upper edge portion of the body ~~21~~. Upper ribs ~~54~~ extending downward are provided at both ends of the side folded part ~~51~~ and the rear folded part ~~52~~, while lower ribs ~~55~~ extending in a vertical direction are provided at a side surface ~~43~~, so that the flange of the rail can be vertically sandwiched with the upper ribs ~~54~~ and the lower ribs ~~55~~.